

| Q.No. | Type | Section | Key/Range | Marks |
|-------|------|---------|--------------|-------|
| 1 | MCQ | GA | D | 1 |
| 2 | MCQ | GA | A | 1 |
| 3 | MCQ | GA | B | 1 |
| 4 | MCQ | GA | A | 1 |
| 5 | MCQ | GA | C | 1 |
| 6 | MCQ | GA | C | 2 |
| 7 | MCQ | GA | C | 2 |
| 8 | MCQ | GA | Marks to All | 2 |
| 9 | MCQ | GA | D | 2 |
| 10 | MCQ | GA | B | 2 |
| 1 | MCQ | PI | A | 1 |
| 2 | MCQ | PI | D | 1 |
| 3 | MCQ | PI | C | 1 |
| 4 | MCQ | PI | B | 1 |
| 5 | MCQ | PI | B | 1 |
| 6 | MCQ | PI | A | 1 |
| 7 | MCQ | PI | B | 1 |
| 8 | MCQ | PI | B | 1 |
| 9 | MCQ | PI | C | 1 |
| 10 | MCQ | PI | D | 1 |
| 11 | MCQ | PI | D | 1 |
| 12 | MCQ | PI | A | 1 |
| 13 | MCQ | PI | B | 1 |
| 14 | MCQ | PI | C | |

| Q.No. | Type | Section | Key/Range | Marks |
|-------|------|---------|--------------|-------|
| 15 | MCQ | PI | C | 1 |
| 16 | NAT | PI | 24.5 to 25.5 | 1 |
| 17 | NAT | PI | 3.49 to 3.51 | 1 |
| 18 | NAT | PI | 0.49 to 0.51 | 1 |
| 19 | NAT | PI | 9.9 to 10.1 | 1 |
| 20 | NAT | PI | 39 to 41 | 1 |
| 21 | NAT | PI | 0.88 to 0.91 | 1 |
| 22 | NAT | PI | 79 to 81 | 1 |
| 23 | NAT | PI | 11.8 to 12.2 | 1 |
| 24 | NAT | PI | 57 to 59 | 1 |
| 25 | NAT | PI | 39 to 41 | 1 |
| 26 | MCQ | PI | A | 2 |
| 27 | MCQ | PI | C | 2 |
| 28 | MCQ | PI | A | 2 |
| 29 | MCQ | PI | D | 2 |
| 30 | MCQ | PI | C | 2 |
| 31 | MCQ | PI | B | 2 |
| 32 | MCQ | PI | D | 2 |
| 33 | MCQ | PI | C | 2 |
| 34 | MCQ | PI | A | 2 |
| 35 | NAT | PI | 675 to 681 | 2 |
| 36 | NAT | PI | 4.52 to 4.56 | 2 |
| 37 | NAT | PI | 990 to 1000 | 2 |
| 38 | NAT | PI | 3.9 to 4.1 | |

| Q.No. | Type | Section | Key/Range | Marks |
|-------|------|---------|----------------|-------|
| 39 | NAT | PI | 3.6 to 4.4 | 2 |
| 40 | NAT | PI | 19800 to 20200 | 2 |
| 41 | NAT | PI | 1575 to 1650 | 2 |
| 42 | NAT | PI | 1.6 to 1.8 | 2 |
| 43 | NAT | PI | 13.9 to 14.1 | 2 |
| 44 | NAT | PI | 6165 to 6175 | 2 |
| 45 | NAT | PI | 2100 to 2155 | 2 |
| 46 | NAT | PI | 2.8 to 3.2 | 2 |
| 47 | NAT | PI | 5.2 to 5.8 | 2 |
| 48 | NAT | PI | 23.8 to 24.2 | 2 |
| 49 | NAT | PI | 7.1 to 7.4 | 2 |
| 50 | NAT | PI | 8.4 to 8.7 | 2 |
| 51 | NAT | PI | 4999 to 5001 | 2 |
| 52 | NAT | PI | 630 to 641 | 2 |
| 53 | NAT | PI | 345 to 351 | 2 |
| 54 | NAT | PI | 53 to 58 | 2 |
| 55 | NAT | PI | 3760 to 7600 | 2 |